


Braco Ring Terminals are designed to offer maximum efficiency under heavy-duty applications. Therefore these terminals are ideal for use in applications which are subject to continuous mechanical vibrations viz. engines, railways, moving components etc. The terminal barrel is brazed and soft annealed, which means that the terminal can be crimped in either direction.

All the terminals are tin plated to avoid oxidization and to achieve maximum corrosion protection.



### COPPER CRIMPING RING TERMINALS (NON-INSULATED)

Size Sq. mm	Dimensions						Code No.
	E	A	C	D	B	J	
10	5.2	4.3	6.3	10	8	20	R - 026
	6.4	4.3	6.3	12	8	23	R - 120
	8.2	4.3	6.3	16	8	27	R - 121
	8.2	4.3	6.3	18	8	30	R - 122
	10.2	4.3	6.3	18	8	30	R - 027
	10.2	4.3	6.3	22	8	34	R - 123
	12.7	4.3	6.3	22	8	34	R - 028
16	5.2	5.6	8.0	10	10	24	R - 124
	5.2	5.6	8.0	12	10	26	R - 125
	6.4	5.6	8.0	12	10	26	R - 029
	6.4	5.6	8.0	16	10	30	R - 126
	8.2	5.6	8.0	16	10	30	R - 030
	9.7	5.6	8.0	16	10	30	R - 031
	8.2	5.6	8.0	18	10	33	R - 127
	10.2	5.6	8.0	18	10	33	R - 032
	10.2	5.6	8.0	22	10	35	R - 128
	12.7	5.6	8.0	22	10	35	R - 033
25	6.4	7.5	11.1	12	11	31	R - 156
	8.2	7.5	11.1	12	11	31	R - 051
	6.4	7.5	11.1	16	11	30	R - 129
	8.2	7.5	11.1	16	11	30	R - 034
	10.2	7.5	11.1	16	11	30	R - 035
	6.4	7.5	11.1	16	11	33	R - 130
	8.2	7.5	11.1	16	11	33	R - 036
	10.2	7.5	11.1	18	11	34	R - 131
	10.2	7.5	11.1	22	11	42	R - 132
	12.7	7.5	11.1	22	11	42	R - 037



## COPPER CRIMPING RING TERMINALS (NON-INSULATED)

Size Sq. mm	Dimensions						Code No.
	E	A	C	D	B	J	
35	6.4	9.0	12.6	16	12	31	R - 133
	8.2	9.0	12.6	16	12	31	R - 038
	8.2	9.0	12.6	18	12	36	R - 134
	10.2	9.0	12.6	18	12	36	R - 039
	10.2	9.0	12.6	22	12	42	R - 135
	12.7	9.0	12.6	22	12	42	R - 040
50	8.2	10.5	14.1	18	16	43	R - 136
	10.2	10.5	14.1	18	16	43	R - 041
	10.2	10.5	14.1	22	16	43	R - 137
	10.2	10.5	14.1	24	16	48	R - 138
	12.7	10.5	14.1	24	16	48	R - 042
	16.2	10.5	14.1	32	16	54	R - 139
70	10.2	12.0	16.0	22	18	47	R - 140
	12.7	12.0	16.0	22	18	47	R - 043
	12.7	12.0	16.0	24	18	48	R - 141
	16.2	12.0	16.0	24	20	54	R - 142
95	10.2	13.5	18.1	22	20	46	R - 143
	10.2	13.5	18.1	24	20	50	R - 144
	12.7	13.5	18.1	24	20	50	R - 044
	16.2	13.5	18.1	28	20	58	R - 145
120	12.7	15.0	20.2	26	22	52	R - 146
	16.2	15.0	20.2	32	22	64	R - 147
	20.3	15.0	20.2	40	22	72	R - 148
150	12.7	16.5	23.7	34	24	66	R - 149
	16.2	16.5	23.7	34	24	66	R - 045
	20.3	16.5	23.7	40	24	74	R - 046

