Braco Copper Long Barrel Tube Terminals are made from high purity copper tube and are annealed to avoid cracking or breaks. The increased barrel length ensures enhanced electrical and mechanical performance in heavy duty application. The absence of an inspection hole prevents the entry of water or moisture into crimped joints making them suitable for outdoor applications. The terminals are tin plated to avoid oxidization and to achieve maximum corrossion protection.



The increased barrel length ensures enhanced electrical and mechanical performance in heavy duty application. The absence of an inspection hole prevents the entry of water or moisture into crimped joints making them suitable for outdoor applications. The terminals are tin plated to avoid oxidization and to achieve maximum corrossion protection.

COPPER CRIMPING TERMINALS FOR COPPER CONDUCTORS (LONG BARREL)

Material Copper BS :1977 Finish : Electro Tinned

| Size Sq. mm | Dimensions | | | | | | |
|----------------|------------|------|------|----|-----|-----|----------|
| | Е | А | С | D | В | J | Code No. |
| 25 | 8.2 | 6.8 | 8.8 | 13 | 16 | 41 | CT-82 |
| 35 | 8.2 | 8.2 | 10.6 | 15 | 20 | 48 | CT-83 |
| 50 | 8.2 | 9.5 | 12.4 | 17 | 26 | 59 | CT-84 |
| 70 | 10.5 | 11.2 | 14.7 | 20 | 28 | 66 | CT-85 |
| 95 | 12.7 | 13.5 | 17.4 | 24 | 32 | 74 | CT-86 |
| 120 | 12.7 | 15 | 19.4 | 28 | 35 | 82 | CT-87 |
| 150 | 12.7 | 16.5 | 21.2 | 30 | 38 | 86 | CT-88 |
| 185 | 12.7 | 18.5 | 23.5 | 34 | 43 | 95 | CT-89 |
| 240 | 16.2 | 21 | 26.5 | 38 | 50 | 112 | CT-90 |
| 300 | 16.2 | 23.5 | 30 | 43 | 55 | 120 | CT-91 |
| 400 | 20.3 | 26.8 | 34.8 | 50 | 58 | 135 | CT-92 |
| 500 | 21 | 30 | 39 | 56 | 70 | 150 | CT-93 |
| 630 | 21 | 35 | 45 | 65 | 76 | 165 | CT-94 |
| 800 | | 39 | 50.5 | 73 | 105 | 200 | CT-95 |
| 1000 | | 43 | 53.7 | 81 | 130 | 240 | CT-96 |

